

Single-lever operation: Inflation, deflation and checking with a single handle.

These pressure gauges are effectively protected against shock and impact by means of a free-standing plastic cap. They can be loaded against gauge pressure and up to the maximum scale value.
With push-in plug for DN 7.2 coupling.

To check lever in home position
To deflate lever actuated half-way
To inflate lever fully actuated

Operating temperature -10 °C to +60 °C

Handheld tyre gauges with tyre valve connector

Art. No.	Type No.	Measuring range	Weight kg	Description
114514	36.011	0 to 4 bar / 56 psi	1.051	calibrated
114515	36.012	0 to 4 bar / 56 psi	1.025	uncalibrated
114516	36.013	0 to 12 bar / 170 psi	1.033	calibrated
114517	36.014	0 to 12 bar / 170 psi	1.046	uncalibrated
114518	36.015	0 to 25 bar / 350 psi	1.054	not conformity assessed



36.013

Handheld tyre gauges with twin hold-on connector

Art. No.	Type No.	Measuring range	Weight kg	Description
-	37.012	0 to 4 bar / 56 psi	1.153	uncalibrated
114519	37.013	0 to 12 bar / 170 psi	1.151	calibrated
114520	37.014	0 to 12 bar / 170 psi	1.162	uncalibrated
114521	37.015	0 to 25 bar / 350 psi	1.110	not conformity assessed



37.013

Handheld tyre gauges with clip-on connector

Art. No.	Type No.	Measuring range	Weight kg	Description
114522	34.011	0 to 4 bar / 56 psi	1.039	calibrated
114523	34.012	0 to 4 bar / 56 psi	1.042	uncalibrated
114524	34.013	0 to 12 bar / 170 psi	1.039	calibrated
114525	34.014	0 to 12 bar / 170 psi	1.079	uncalibrated



34.014

Connector

Art. No.	Type No.	Description
114530	36.030	Tyre valve connector
114531	36.020	Clip-on connector
114532	37.030	Twin hold-on connector



36.030

Replacement hoses

Art. No.	Type No.	Description
114534	36.250	Hose, complete with tyre valve connector for 36.011 - 36.015 gauges
114536	37.250	Hose, complete with twin hold-on connector for 37.011 - 37.015 gauges
114538	38.250	Hose, complete with clip-on connector for 34.011 to 34.014 gauges



36.250

Pressure gauges

Art. No.	Type No.	Description
114540	36.40	Pressure gauge 0 to 4 bar/50 psi 80 mm Ø, for plugging for 36.011 - 36.012 gauges
114541	36.42	Pressure gauge 0 to 12 bar/170 psi 80 mm Ø, for plugging for 36.013 - 36.014 gauges
114542	36.43	Pressure gauge 0 to 25 bar/350 psi 80 mm Ø, for plugging for 36.015 gauge



36.42