

Brass, not type-tested.

Manual adjustment of the blow-off pressure (lock nut).

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

Material

Swivels MS 58

Spring 1.4310

Operating pressure


0,5 to 60 bar

Operating temperature

-20 °C bis 180 °C

Seal

FKM



218.11

Mini blow-off valves brass, G 1/8									
Art. No.	Ident No.	Thread	Set pressure	Blow-off rate	C mm	D mm	a/f mm	do mm	Weight kg
218.10	103901	G 1/8	0.5 – 1.0 bar	to 50 l/min	27.0 – 34.0	7.0	16	3.0	0.031
218.11	103902	G 1/8	1.0 – 4.0 bar	to 200 l/min	27.0 – 34.0	7.0	16	3.0	0.032
218.12	103903	G 1/8	3.0 – 7.0 bar	to 350 l/min	27.0 – 34.0	7.0	16	3.0	0.033
218.13	103904	G 1/8	6.0 – 12.0 bar	to 650 l/min	27.0 – 34.0	7.0	16	3.0	0.034
218.14	103905	G 1/8	10.0 – 18.0 bar	to 870 l/min	27.0 – 34.0	7.0	16	3.0	0.032
218.15	103906	G 1/8	16.0 – 32.0 bar	to 1600 l/min	27.0 – 34.0	7.0	16	3.0	0.033
218.16	103907	G 1/8	30.0 – 60.0 bar	to 3000 l/min	27.0 – 34.0	7.0	16	3.0	0.034

Mini blow-off valves brass, G 1/4									
Art. No.	Ident No.	Thread	Set pressure	Blow-off rate	C mm	D mm	a/f mm	do mm	Weight kg
218.20	103908	G 1/4	0.5 – 1.0 bar	to 50 l/min	27.0 – 34.0	7.0	16	3.0	0.035
218.21	103909	G 1/4	1.0 – 4.0 bar	to 200 l/min	27.0 – 34.0	7.0	16	3.0	0.035
218.22	103910	G 1/4	3.0 – 7.0 bar	to 350 l/min	27.0 – 34.0	7.0	16	3.0	0.035
218.23	103911	G 1/4	6.0 – 12.0 bar	to 650 l/min	27.0 – 34.0	7.0	16	3.0	0.036
218.24	103912	G 1/4	10.0 – 18.0 bar	to 870 l/min	27.0 – 34.0	7.0	16	3.0	0.036
218.25	103913	G 1/4	16.0 – 32.0 bar	to 1600 l/min	27.0 – 34.0	7.0	16	3.0	0.036
218.26	103914	G 1/4	30.0 – 60.0 bar	to 3000 l/min	27.0 – 34.0	7.0	16	3.0	0.037