

Premium quality screwdrivers for the professional user

Superior S2 steel hexagonal shaft for higher torque & wear resistance

Shaft extends into the handle, ensuring full transfer of force.

Multi-component injection moulded hexagonal grip is non-slip & does not roll away

Magnetised tip is accurately hardened ensuring long lasting durability

Tip has black oxide finish for enhanced corrosion resistance



S2 STEEL	HARDENED	HEX SHANK
<b>S2</b>	58-62 HRC	

### ORDERING INFORMATION

CAT NR.	ORD NR.	TYPE	SIZE	L1	L2	H
				(MM)	(MM)	(MM)
SCDR/H/FL3/75	33735		0.5x3.0	75	75	4
SCDR/H/FL4/100	33736		0.8x4.0	100	98	4
SCDR/H/FL6.5/38	33734		1.2x6.5	38	55	6
SCDR/H/FL6.5/100	33737		1.2x6.5	100	108	6
SCDR/H/FL6.5/150	33738		1.2x6.5	150	108	6
SCDR/H/FL8/150	33739		1.6x8.0	150	118	8
SCDR/H/PH1/75	33731		PH1	75	98	5
SCDR/H/PH2/38	33730		PH2	38	55	6
SCDR/H/PH2/100	33732		PH2	100	108	6
SCDR/H/PH3/150	33733		PH3	150	118	8
◆SCDR/H/6/ST	33745			Set of 6: PH 1x75, PH 2x100, FL 3x75, FL 4x100, FL 6.5x150 & FL 8x150		

◆ New



Hex shaft can be tightened using a spanner for high torque applications