

53

“DRIVE FIT” GREASE FITTING INSTALLER

Specialty tools for installing straight & angled Drive-Fit Grease fittings into untapped holes

Steel construction in zinc plated finish



CAT. NR.	ORD. NR.	FOR FITTING TYPE
FTS/01	44892	Straight
FTA/01	44893	Angled

54

GREASE FITTING UNBLOCKER

GFU

Opens clogged grease fittings and loosens hardened grease joints

Excellent for maintaining and protecting bearings, control arms, joints, king pins, etc.

Tool has an all steel construction & is designed to be tapped with a hammer to force a light viscosity oil through the tool into the coupler & finally into the grease joint, breaking up and removing dirt and debris

Built-In Hand Guard for added safety in use

Flexible hose attachment reaches fittings in difficult areas

Comes complete with grease coupler and 2 spare seals for replacing the piston seals as they wear out



CAT. NR.	ORD. NR.
GFU/01	44894

QUICK CONNECTION SYSTEM

*Quick Connect!
Connect or disconnect
with a snap!*

A simple and effective system that renders versatility to Grease Guns

Greasing in inaccessible, difficult to reach areas becomes very convenient with the use of any of the Quick Link accessories. No threads, no screwing or unscrewing, just snap on and use on sealed bearings, U-joints, high-pressure insert fittings and recessed fittings

Ready to use range is detailed in the following pages. Various other combinations, however can be devised based on specific application and need

The system is suitable for use with hand operated grease guns only



STEP 1
Retract sleeve of the quick connect system



STEP 2
Snap on the system by simply "Plugging On" the grease fitting to the coupler



STEP 3
Ensure that the quick connect system is secure



STEP 4
Release the sleeve of the quick connect system. The sleeve automatically slides over the coupler to encase it securely

To disconnect, simply reverse the operation

55

QUICK CONNECT ADAPTORS



FOR HAND OPERATED
GREASE GUN

DNN/1-8/90/Q



**1,000 PSI
(69 BAR)**



Quick Connect Right Angled Needle Nose Dispenser for dispensing a fine line of grease. The right angled design allows convenient access in shoulders & other confined areas

CAT. NR.

ORD. NR.

DNN/1-8/90/Q

44913

HC/14/4/90/Q



**6,000 PSI
(413 BAR)**



Quick Connect Right angled Grease Coupler Right angle coupler fitted onto the quick disconnect adaptor. For quickly converting regular couplers for greasing fittings with limited access, in low height areas etc. Fits straight onto the grease gun coupler

CAT. NR.

ORD. NR.

HC/14/4/90/Q

44912

GIN/01/Q



**1,000 PSI
(69 BAR)**



Quick Connect Grease Injector Needle useful for lubricating in very tight spaces such as sealed bearings, universal joints etc. Comes complete with protective plastic holder

CAT. NR.

ORD. NR.

GIN/01/Q

44914