

# 1/2" Angle Impact Wrench Standard

**IPW-ANG**

Robust & durable aluminium housing

Stubby style wrench ideal to use in confined spaces

Jumbo Hammer Impact Mechanism for instant high torque output for tough applications

3 speed position control to adjust tool speed for varying applications; both in forward & reverse directions

Reduced vibrations(50%) & increased torque output(20%) compared to other geared angle impact wrenches


360° Swivelling exhaust

**Ideal for use in**

- a. General automotive repair & service center for passenger vehicles
- b. Assembly lines for 4 wheeler & LCV's
- c. MRO jobs in railways
- d. Repair & maintenance of gear units & boxes
- e. Repair & maintenance of printing press machines
- f. Assembly lines for white goods (fans, washing machines etc.)



MAX TORQUE*	FREE SPEED	NET WEIGHT	AVG. AIR CONSUMPTION	ALUMINIUM BODY	MAX. NUT CAPACITY
<b>678 Nm</b> (500 ft-lb) <small>*@15 Sec.</small>	<b>6,500 RPM</b>	<b>1.4 KG</b> (3.09 LB)	<b>4.2 CFM</b> (119 LPM)	<b>AI</b>	<b>M16</b>



Jumbo Hammer Mechanism



360° Swivelling Exhaust



3 Speed Position Control

**ORDERING INFORMATION**

CAT NR.	ORD NR.	FREE SPEED	MAX. TORQUE		AIR INLET SIZE	AIR HOSE I.D.	AVG. AIR CONSUMPTION		OVERALL LENGTH		NET WEIGHT	
		(RPM)	(FT-LB)	(NM)	(INCH)	(INCH)	(CFM)	(LPM)	(INCH)	(MM)	(KG)	(LB)
IPW/1-2/ANG	61924	6500	500	678	1/4	3/8	4.2	119	9.76	248	1.4	3.09

\*@15 SEC