

## Variable-control blow guns

Art. No. 114390 to 114408

P 7-49 e

Plastic, with noise-reducing Star-Tip nozzle.

Ergonomic grip with a very high blowing force. Several possible hanging points thanks to the modified handle. Robust yet lightweight for a long service life. With its ergonomic design, the gun can be used by both left and right-handed users!

Material POM

Tube Nickel-plated brass

Connection thread Rc 1/4

Max. operating pressure16 bar (232 PSI)Max. bursting pressure64 bar (928 PSI)Temperature range-20 °C to 60 °C

Airflow 500 l/min (17,7 CFM) (Series 37) 190 l/min (6,7 CFM) (Series 38) Noise level

Noise level 96 dB (Series 37), 79 dB (Series 38) Thread Nozzle side (male thread) M14x1



Blow gun, stepless adjustment, for use with extension tubes, without nozzle						
Art. No.	Type No.	Type of connection				
114390	36 A	Stem, I.D. 6				
114391	36 B	Stem, I.D. 9				
114392	36 C	Stem, I.D. 13				
118433	36 K/T	Rc 1/4 IT				
114393	36 K	Push-in plug for DN 7.2 - 7.8 couplings				


Blow gun, stepless adjustment, 90 mm tube						
Art. No.	Type No.	Type of connection				
114394	37 A	Stem, I.D. 6				
114395	37 B	Stem, I.D. 9				
114396	37 C	Stem, I.D. 13				
118465	37 V	Rc 1/4 IT				
114397	37 K	Push-in plug for DN 7.2 - 7.8 couplings				

Blow gun, stepless adjustment, with noise-reducing Star-Tip nozzle, 90 mm tube							
Art. No.	Type No.	Type of connection					
114398	38 A	Stem, I.D. 6					
114399	38 B	Stem, I.D. 9					
114400	38 C	Stem, I.D. 13					
118485	38 V	Rc 1/4 IT					
114401	38 K	Push-in plug for DN 7.2 - 7.8 couplings					





Extension	Extension tube for basis blow guns		
Art. No.	Type No.	Designation	
114402	37.090	Blow pipe with standard nozzle, 90 mm, bent	
114403	37.300	Extension tube with standard nozzle, 300 mm, straight	
114404	37.500	Extension tube with standard nozzle, 500 mm, straight	
114405	37.400	Flexible extension tube with standard nozzle, 400 mm, bendable	
114406	38.090	Blow pipe with Star-Tip nozzle, 90 mm, bent	
114407	38.300	Extension tube with noise-reducing Star-Tip nozzle, 300 mm straight	
114408	38.500	Extension tube with noise-reducing Star-Tip nozzle, 500 mm straight	



RIEGLER & Co. KG, Sales Engineering Schützenstraße 27 | 72574 Bad Urach Phone +49 7125 9497-642 technik@riegler.de edition 01/2024

page 1 from 2

## Variable-control blow guns Art. No. 114390 to 114408



Accessories for plastic blow guns			
Art. No.	Type No.	Designation	
114413	378.01	Set of rubber-tip nozzles (Ø 14, 25, 35 mm) for sensitive surfaces fit directly onto the tube	
135938	378.01-14	Rubber nozzle Ø 14 mm to plug onto the pipe	
135939	378.01-25	Rubber nozzle Ø 25 mm to plug onto the pipe	
135940	378.01-35	Rubber nozzle Ø 35 mm to plug onto the pipe	
114414	378.02	Chip shield, (Ø 100 mm) fits directly onto the tube	
114415	378.03	Silencer nozzle, fits directly onto the tube. Noise reducing	
114416	378.04	Venturi nozzle for deflecting lightweight chips. Fits directly onto the tube	
114417	378.05	Bypass nozzle reduces the output pressure to a safe value in case of back pressure. Fits directly onto the tube.	
114418	378.06	Air curtain nozzle: Creates a protective air curtain that is suitable for deflecting lightweight wood chips or fluids. Fits directly onto the tube	
114419	378.07	Silencer nozzle for reducing noise. Specially designed for use when space is limited. Fits directly onto the thread of the blow gun body (only for blow guns series 40)	
114389	MH-41	Magnet holder (for air and fluid gun and plastic blow guns)	





















